22

PATENT CLAIMS
    1. A device for recording of information by imaging on
a light-sensitive sensor (8) for obtaining at least two
images of said information having partially overlapping
5   contents, c h a r a c t e r i z e d by
    a processing device for converting the information in
each of said images to a coded representation,
    a comparision device for comparing the coded
representation of said images for determining an overlap
10 position between the images;
    an assemblying device comprising a memory for
assemblying said coded representation to form a composite
representation in said memory.
    2. A device as claimed in claim 1, c h a r a c -
15 t e r i z e d in that said coded representation is a
character code, such as ASCII.
    3. A device as claimed in claim 1, c h a r a c -
t e r i z e d in that said coded representation comprises a
division of the information inside boarders, such as
20 rectangles, each comprising portions of the information.
    4. A device as claimed in claim 3, c h a r a c -
t e r i z e d in that said rectangles comprises words
included in said information.
    5. A device as claimed in claim 4, c h a r a c -
25 t e r i z e d by a character recognition device for
processing the composite representation and converting it to
character code format, such as ASCII.
    6. A device as claimed in claim 4, c h a r a c -
t e r i z e d by a character recognition device for
30 processing each image and converting it to character code
format, such as ASCII.
    7. A device as claimed in claim claim 1, c h a r a c -
t e r i z e d by
    a determining device for determing structures in each
35 of said images, such as direction of lines.
    8. A device as claimed in claim 7, c h a r a c -

t e r i z e d in that said determining device is adapted to
identify direction of lines in each of said images.

9. A device as claimed in claim 8, c h a r a c -
t e r i z e d in that said determining device is adapted to
5   identify text line directions.

10. A device as claimed in claim 8 or 9, c h a r a c -
t e r i z e d in that the determination device is adapted to
identify direction of lines and text line directions by
means of a Hough transformation of each image.

10   11. A method for recording information by imaging on a
light-sensitive sensor for obtaining at least two images of
said information having partially overlapping contents,
c h a r a c t e r i z e d by
converting the information in each of said images·to a
15   coded representation,
comparing the coded representation of said images for
determining an overlap position;
assembling said coded representations to form a
composite representation.

20   12. A method as claimed in claim 11, c h a r a c -
t e r i z e d in that said coded representation is a
character code, such as ASCII.

13. A method as claimed in claim 11, c h a r a c
t e r i z e d in that said coded representation comprises a
25   division of the information in rectangles each comprising
portions of the information.

14. A method as claimed in claim 13, c h a r a c -
t e r i z e d in that said rectangles comprises words
included in said information.

30   15. A method as claimed in claim 14, c h a r a c -
t e r i z e d by processing the composite representation and
converting it to a character code format, such as ASCII.

16. A method as claimed in claim 14, c h a r a c -
t e r i z e d by processing each image and converting it to
35   character code format, such as ASCII.

17. A method as claimed in claim claim 11 c h a r a c -

24

t e r i z e d by

determing structures in each of said images, such as
direction of lines.

18. A method as claimed in claim 17, c h a r a c -
5   t e r i z e d by identifying direction of lines in each of
said images.

19. A method as claimed in claim 18, c h a r a c -
t e r i z e d by identifying text line directions.

20. A method as claimed in claim 19, c h a r a c -
10 t e r i z e d by identifying direction of lines by means of
Hough transformation of each image.

21. A method as claimed in claim 20, c h a r a c -
t e r i z e d by adjusting the perspective of each image in
dependence of the direction of lines.

15 22. A method as claimed in claim 20, c h a r a c -
t e r i z e d by adjusting the rotational position of each
image in dependence of the direction of lines.

23. A computer program for carrying out the method
according to any of claims 11-22.